









PREISOLATI

INSULATED TERMINALS - COSSES ISOLÉES - ISOLIERTE KABELSCHUHE



Push on

DISEGNO DRAWING DESSIN ZEICHNUNG	SEZIONE CAVO CABLE SECTION SECTION DU CÂBLE KABEL QUERSCHNITT mm ²	L mm	S mm	SPESSORE THICKNESS ÉPAISSEUR DICKE mm	MATERIALE MATERIAL MATÉRIEL WERKSTOFF	REF.	PCS
	0.25÷1	2.8	0.5	0.3	CuZn-Sn PVC	18.50200 18.50209	100 1000
	0.25÷1	2.8	0.8	0.3	CuZn-Sn PVC	18.50400 18.50409	100 1000
	1÷2.5	2.8	0.5	0.3	CuZn-Sn PVC	18.54200 18.54209	100 1000
	1÷2.5	2.8	0.8	0.3	CuZn-Sn PVC	18.54400 18.54409	100 1000
	0.25÷1	4.7	0.5	0.4	CuZn-Sn PVC	18.50500 18.50509	100 1000
	0.25÷1	4.7	0.8	0.4	CuZn-Sn PVC	18.50300 18.50309	100 1000
	1÷2.5	4.7	0.5	0.4	CuZn-Sn PVC	18.54500 18.54509	100 1000
	1÷2.5	4.7	0.8	0.4	CuZn-Sn PVC	18.54300 18.54309	100 1000
	0.25÷1	4.7	0.5	0.4	CuZn-Sn PVC	18.51400 18.51409	100 1000
	1÷2.5	4.7	0.5	0.4	CuZn-Sn PVC	18.55400 18.55409	100 1000
	0.25÷1	6.3	0.8	0.4	CuZn-Sn PVC	18.51000 18.51009	100 1000
	1÷2.5	6.3	0.8	0.4	CuZn-Sn PVC	18.55000 18.55009	100 1000