



Article
reference

Article no.
Consumer unit



XENAELECTRON® for XENARC® electronic gas discharge headlight lamps

XENAELECTRON® XT5-1-D1/12V	4008321015686	D1S & D1R	12	500	3.4	41 ¹⁾	-40 ... 105
XENAELECTRON® XT5-3-D1/12V TAB	4008321015709	D1S & D1R	12	500	3.4	41 ¹⁾	-40 ... 105
XENAELECTRON® XT5-1-D1/24V	4008321139047	D1S & D1R	24	500	1.7	41 ¹⁾	-40 ... 105
XENAELECTRON® XT5-3-D1/24V TAB	4008321139023	D1S & D1R	24	500	1.7	41 ¹⁾	-40 ... 105
XENAELECTRON® XT5-3-D3/12V TAB	Projected	D3S	12	500	3.5	42 ²⁾	-40 ... 105

Article
reference



Article no.
Shipping unit



XENAELECTRON® XT5-1-D1/12V	82	73	25	106	1	4008321044297	40
XENAELECTRON® XT5-3-D1/12V TAB	125	74	25	116	2	4008321044310	40
XENAELECTRON® XT5-1-D1/24V	82	73	25	106	1	4008321139054	40
XENAELECTRON® XT5-3-D1/24V TAB	125	74	25	116	2	4008321139030	40
XENAELECTRON® XT5-3-D3/12V TAB	125	74	25	116	2	Projected	40

The control gear complies with type of protection IP X7.

The OSRAM D1/D3 system consists of OSRAM XENAELECTRON® XT5-D1/12V or OSRAM XENAELECTRON® XT5-D3/12V control gear for mercury-free gas discharge lamps (XENARC® D3), a connecting cable between the control gear and the lamp, and the OSRAM D1/D3 XENARC® electronic lamp.

Caution: Because of their high voltage, XENARC® and XENAELECTRON® products may only be used in combination with one another and may only be replaced at authorised workshops. Improper use in vehicles may make the vehicle illegal and therefore not covered by insurance.

D1 and D3 HID system properties.

- Perfectly matched to OEM automotive requirements.
- Compact design of the XENAELECTRON® control gear.
- Reduction in high voltage on the connecting cable by a factor of more than 20 compared with a D2 system.
- Highly flexible connecting cable between the control gear and the lamp.
- Elimination of the costly and critical high-voltage plug connections on the lamp.
- Optimised and integrated high-voltage igniter in the protected lamp base.
- Tried and tested lamp technology based on the D2/D4 lamp

1) For operating an OSRAM D1 XENARC® electronic 35W gas discharge lamp.
2) For operating an OSRAM D3 XENARC® electronic 35W gas discharge lamp.

XENARC® electronic D1S/R, the XENAELECTRON® control gear and the associated connecting cables form a perfectly matched system from OSRAM.